



Declaration of Performance

Website: www.jindalstainless.com

DOP No. JSLO/1.4512/CR

Sr. No	Performance Particulars		Description		
1	Identification Code		EN 10088-4: 2009, Cold rolled Strip and Plate/Sheet of 1.4512		
2	Batch No. / Serial No. acc. To article 11 par. 4		As per Mill Test certificate Marking/ Label/ Hand punch		
3	Intended use of construction products:		Metal structures or in composite metal and concrete structures		
4	Contact address of manufacturer: acc. To article 11 par. 5		JINDAL STAINLESS LIMITED Kalinga Nagar Industrial Complex, Danagadi, Jajpur, 755026, Odisha, India		
5	Contact address of authorized representative: acc. To article 12 par. 2		HOD Quality Assurance Department Jindal Stainless Limited, Jajpur, Kalinga Nagar Industrial Complex, Danagadi, Jajpur, 755026, Odisha, India		
6	Assessment system and verification for constancy of performance acc. To annex V		System 2+		
7	Declaration of performance concerning a construction product covered by a harmonized standard		TUV NORD Systems GmbH & Co. KG, notified body for construction product regulation (CPR), Reg No. 0045 performed initial inspection of manufacturing plant under system 2+ and issued certificate of conformity of the factory production control		
8	Construction product with European Technical Assessment:		NA		
9	Declared Performance				
Essential Characteristics Per			formance	Harmonized Technical specification	
			EN ISO 9445		
Mechanical Properties					
	Yield Strength(MPa)		rolled strip = 220 Min. (0.2%)		
Tensile Strength(MPa)		Cold rolled strip = 380 - 560			
Elongation (%)		Minimum 25%			
Impact Strength		NA Satisfactory			
Weldability (Cover by Chemical		Satis	ractory	EN 10000 4.2000	
Composition) Durability (Cover by Chemical S		Catio	factory	EN 10088-4:2009	
Composition)		Saus	oracior y		
		NA			
Strei		11/1			
			factory		
	Dangerous Substance		Onnm		

Dangerous Substance < 100ppm

10. The performance of the product identified in points 1 and 2(i. e. serial no.) is in conformity with the declared performance in point 9(i. e serial no.). The Declaration of Performance is issued under the sole responsibility of the manufacturer identified in point 4.

Nagaraj



Declaration of Performance

Website: www.jindalstainless.com

DOP No. JSLO/1.4512/HR/S

Sr. No	Performance Particulars		Description			
1	Identification Code		EN 10088-4: 2009, Hot rolled sheet and strip of 1.4512			
2	Batch No. / Serial No. acc. To article 11 par. 4		As per Mill Test certificate Marking/ Label/ Hand punch			
3	Intended use of construction products:		Metal structures or in composite metal and concrete structures			
4	Contact address of manufacturer: acc. To article 11 par. 5		JINDAL STAINLESS LIMITED Kalinga Nagar Industrial Complex, Danagadi, Jajpur, 755026, Odisha, India			
5	Contact address of authorized representative: acc. To article 12 par. 2		HOD Quality Assurance Department Jindal Stainless Limited, Jajpur, Kalinga Nagar Industrial Complex, Danagadi, Jajpur, 755026, Odisha, India			
6	Assessment system and verification for constancy of performance acc. To annex V		System 2+			
7	Declaration of performance concerning a construction product covered by a harmonized standard		TUV NORD Systems GmbH & Co. KG, notified body for construction product regulation (CPR), Reg No. 0045 performed initial inspection of manufacturing plant under system 2+ and issued certificate of conformity of the factory production control			
8	Construction product with European Technical Assessment:		NA			
9	Declared Performance					
Essential Characteristics		Per	formance	Harmonized Technical specification		
Tole	Tolerances on dimensions and shape		EN ISO 9444			
Mecl	nanical Properties					
Yield	Yield Strength(MPa)		rolled strip = 220 Min. (0.2%)			
Tens	Tensile Strength(MPa)		rolled strip = 380 - 560			
Elon	Elongation (%)		mum 25%			
Impa	Impact Strength					
Weld	Weldability (Cover by Chemical		sfactory			
	position)		•	EN 10088-4:2009		
	Durability (Cover by Chemical		factory			
	Composition)					
Frac	Fracture Toughness (Cover by Impact N					
	Strength)					
Cold	Cold Formability		factory			
Dang	gerous Substance	< 10	0ppm			

^{10.} The performance of the product identified in points 1 and 2(i. e. serial no.) is in conformity with the declared performance in point 9(i. e serial no.). **The Declaration of Performance is issued under the sole responsibility of the manufacturer identified in point 4.**

Nagaraj